C440E TWIN MOUNT CARDIOID CONDENSER MICROPHONES Cardioid Condenser Microphones mounted on twin rigid shafts each vertically adjustable through 180+ degrees. Designed for use in a wide range of applications including presentations, conferences, broadcasting and places of worship.

CLOCKAUDIO




- Attractive slimline design
- Optimised for consistent sound quality
- Shaft angles independently adjustable
- XLR mounting
- Engineered in high quality brass
- Finished in satin black


TWIN MOUNT CARDIOID CONDENSER MICROPHONES

CLOCKAUDIO

C440E SPECIFICATIONS

TYPE	Condenser (back electret)
POLAR PATTERN	Cardioid
FREQUENCY RESPONSE	50Hz - 18KHz
SENSITIVITY	-44dB \pm 3dB at IKHz (OdB = IV/Pa)
IMPEDANCE	200 Ohms
S/N RATIO	64dB(A)
MAXIMUM SPL	125dB 1% THD
POWER	9 - 48 Volts Phantom Power
SWITCHABLE BASS FILTER	-4dB per octave at 400Hz to -6dB per octave at 100Hz
SWITCHABLE PAD	-10dB
TERMINATION	Male 3 pin XLR
FINISH	Satin Black
ACCESSORIES	W2 foam windshields included
DIMENSIONS	450mm Overall Length 7mm diameter Rigid Shafts





CLOCKAUDIO

9 Stratfield Park, Elettra Avenue, Waterlooville, Hampshire PO7 7XN Tel +44 (0)23 9225 1193 Fax +44 (0)23 9225 1201 E-mail sales@clockaudio.demon.co.uk www.clockaudio.demon.co.uk



PROFESSIONAL