

**CLOCKAUDIO**



**CLOCKAUDIO**

9 Stratfield Park, Elettra Avenue, Waterlooville, Hampshire PO7 7XN  
Tel +44 (0)23 9225 1193 Fax +44 (0)23 9225 1201  
E-mail [sales@clockaudio.demon.co.uk](mailto:sales@clockaudio.demon.co.uk) [www.clockaudio.demon.co.uk](http://www.clockaudio.demon.co.uk)




As part of a continuous product improvement programme, we reserve the right to alter specifications without prior notice.

TheCWEAgency 023 9248 6566 [www.thecwagency.com](http://www.thecwagency.com)

PROFESSIONAL  
MICROPHONE  
SYSTEMS

**CLOCKAUDIO**

C900  
COMBINATION  
SERIES:  
MICROPHONES  
STANDS &  
SHAFTS



PROFESSIONAL  
MICROPHONE  
SYSTEMS



C900  
COMBINATION  
SERIES:  
MICROPHONES  
STANDS &  
SHAFTS




C900

- Designed as a rugged wide band Cardioid Microphone for multiple uses.
- Wide band response
  - Built in pop shield
  - Easy click connection with combination stands & shafts accessories
  - Engineered in high quality brass
  - Satin Black finish

SPECIFICATIONS

TYPE	Condenser (back electret)
POLAR PATTERN	Cardioid
FREQUENCY RESPONSE	50 Hz - 20 KHz
SENSITIVITY	-48 dB +/- 3 dB @ 1 KHz (0 dB = 1 V/Pa)
IMPEDANCE	1.8 K Ohms
S/N RATIO	68 dB(A)
MAXIMUM SPL	126 dB
POWER REQUIREMENTS	9 - 48 Volts phantom power via a PPA adaptor
TERMINATION	Switchable 3 pin Tini Q
DIMENSION	57mm x 19mm
FINISH	Satin Black




C3H

- Short slimline Cardioid Condenser Microphone ideal for use in controlled acoustic environments such as conference halls, centres of worship and broadcasting.
- Response optimised for consistent sound quality
  - Superior grade components used throughout
  - Easy click connection with combination stands & shafts accessories
  - Engineered in high quality brass
  - Satin Black finish

SPECIFICATIONS

TYPE	Condenser (back electret)
POLAR PATTERN	Cardioid
FREQUENCY RESPONSE	50 Hz - 18 KHz
SENSITIVITY	-47 dB +/- 3 dB @ 1 KHz (0 dB = 1 V/Pa)
IMPEDANCE	1.8 K Ohms
S/N RATIO	64 dB(A)
MAXIMUM SPL	125 dB 1% THD
POWER REQUIREMENTS	9 - 48 Volts phantom power via a PPA adaptor
TERMINATION	Switchable 3 pin Tini Q
DIMENSION	45mm x 12mm
FINISH	Satin Black




C800H

- Developed for speech purposes in a wide range of pro and live sound applications including places of worship, conference and leisure centres.
- Slim mini shotgun
  - Optimised for speech clarity
  - Superior grade components
  - Easy click connection with combination stands & shafts accessories
  - Unobtrusive slimline design
  - Engineered in high quality brass
  - Satin Black finish

SPECIFICATIONS

TYPE	Condenser (back electret)
POLAR PATTERN	Hyper cardioid
FREQUENCY RESPONSE	50 Hz - 18 KHz
SENSITIVITY	-47 dB +/- 3 dB @ 1 KHz (0 dB = 1 V/Pa)
IMPEDANCE	1.8 K Ohms
S/N RATIO	64 dB(A)
MAXIMUM SPL	125 dB 1% THD
POWER REQUIREMENTS	9 - 48 Volts phantom power via a PPA adaptor
TERMINATION	Switchable 3 pin Tini Q
DIMENSION	151mm with W8 windshield
FINISH	Satin Black



PPA Phantom Power Adaptor

- 9 - 48 Volt power adaptor.
- Switchable Bass cut filter
  - Switchable Pad
  - Fully balanced output
  - Surface mount technology
  - Robust all metal construction
  - Satin Black finish

SPECIFICATIONS

POWER REQUIREMENTS	9 - 48 Volts phantom power
SWITCHABLE BASS FILTER	-4 dB per octave at 400 Hz to -6 dB per octave at 100 Hz
SWITCHABLE PAD	-10 dB
IMPEDANCE	200 Ohms
TERMINATION	Male XLR
FINISH	Satin Black

ACCESSORIES

CA700/CA900

Long rigid shaft (choice of two lengths) and short upright shaft connected by a separate, lockable swivel joint allowing adjustments to angle, height and reach. The long shafts have a Phantom Power Adaptor at the bottom end and knuckle joint at tip with Switchable Tini Q - 3 pin female connector. A bolt and washer are supplied to secure the short shaft to the SM 155 floor mounting shock absorbing base.

Lengths	CA700 Long Shaft	700mm
	CA900 Long Shaft	1200mm
Terminations	Short Shaft	350mm
	Long Shafts	Bottom end - Male 3 pin XLR Tip - Switchcraft Tini Q 3 pin female connector
Finish	Satin Black	

SM 155

Floor mounting shock absorbing microphone base.

Height	42.5mm
Base Diameter	155mm
Finish	Satin Black

CA30/CA40

Semi rigid 300mm or 400mm shafts fitted with Phantom Power Adaptor at the bottom end and knuckle joint at tip with Switchcraft Tini Q - 3 pin female connector.

Lengths	CA30	300mm
	CA40	400mm
Terminations	Bottom end	- Male 3 pin XLR
	Tip	- Switchcraft Tini Q 3 pin female connector
Finish	Satin Black	

CAK 1

Phantom Power Adaptor with knuckle joint and Switchcraft Tini Q - 3 pin female connector.

Height	160mm including Switchcraft connector
Finish	Satin Black

S750

Table microphone base fitted with Tini Q - 3 pin female connector and 3 metres of cable requiring a Phantom Power Adaptor.

Height	70mm including Switchcraft connector
Base Diameter	75mm
Finish	Satin Black