

GT402T HAND HELD TRANSMITTER



System FM Carrier	UHF PLL Synthesized
Frequency Range	740 MHz - 865 MHz (Bands according to regulation)
Channel Frequencies	16 Pre-programmed Switchable
Frequency Stability	+ 0.005%
Maximum Deviation	+ -50 KHz with level limiting
Dynamic Range	<80dB
Powering	2 x AA Ni-MH batteries averaging 10 hours use on full charge

DC320 CHARGING FLIGHT CASE



GT502T TRANSMITTER



System FM Carrier	UHF PLL Synthesized
Frequency Range	UHF 740 MHz - 865 MHz (Bands according to regulation)
Channel Frequencies	16 Pre-programmed Switchable
Frequency Stability	+ 0.005%
Maximum Deviation	+ -50 KHz with level limiting
Dynamic Range	<80dB
Powering	External 12V DC 500MA AC Adaptor 115V - 230V AC

Capacity	20 (Receiver or Transmitter Belt Style only)
Indicator LED	Red Charging Green Fully Charged
Charging Current	120 mA
Charging Time	NI-MH (1300 mAh) 10 - 12 hours
Charging Control	PWM (Timer Power Off Detector)

- DC 302 2 unit desktop charger
(for Hand Held or Belt Style Transmitter/ Receiver)
- DC 310 10 unit charger in fitted flight case