

CLOCKAUDIO

STANDS

SM20

SM 75

SM I 10

S I 20 X

S I 20 S



SM 75



SM I 10



SM 20



S I 20 S



S I 20 X

PROFESSIONAL
MICROPHONE
SYSTEMS

SPECIFICATIONS

STANDS

SM20

SM 75

SM I 10

S I 20 X

S I 20 S

S120

Table Microphone Base fitted with M10 x 1 screw thread mounting hole

S120S

As above but fitted with Press to Talk or Latching Switch

S120X

Table Microphone Base fitted with XLR Connector

S120XS

As S120X but fitted with Press to Talk or Latching Switch

HEIGHT	S120 / S120S S120X / S120XS	32mm 57mm including XLR
BASE DIAMETER	120mm	
CAVITY	The base has a cavity that can be accessed from the bottom via a metal plate secured by three screws. The space available, approx 74mm x 22.5mm, would be suitable for mounting additional electronics.	
WEIGHT	1.87 Kilos	
FINISH	Satin Black	

SM 75

Microphone Shock Absorbing Base for permanent fixing above or below the surface. Supplied complete with Female XLR and conversion adaptor for 3/8" BSW or 10mm screw fittings.

HEIGHT	32mm/64mm including XLR
BASE DIAMETER	75mm
WEIGHT	530 gms
FINISH	Satin Black

SM I 10

Shock absorbing table microphone stand.

HEIGHT	85mm including microphone holder
BASE DIAMETER	110mm
WEIGHT	765 gms
FINISH	Satin Black

SM 20

Very low profile through table Microphone Shock Mount with Tini Q Male socket connector and integral Phantom Power Adaptor.

HEIGHT	4mm above surface
SURFACE DIAMETER	29mm
BODY DIAMETER	25mm
BODY LENGTH	86mm below surface top. Lower 63mm with M25 X 1 threaded section to secure. Nut supplied.
FINISH	Top - Satin Black/Body - Brass

INTEGRAL PHANTOM POWER ADAPTOR

IMPEDANCE	200 Ohms
POWER REQUIREMENTS	9 - 48 volts phantom power
SWITCHABLE BASS FILTER	-4dB per octave @ 400Hz to -6dB per octave @ 100Hz
SWITCHABLE PAD	-10dB
TERMINATION	Male 3 pin XLR

CLOCKAUDIO

9 Stratfield Park, Elettra Avenue, Waterlooville, Hampshire PO7 7XN
Tel +44 (0)23 9225 1193 Fax +44 (0)23 9225 1201
E-mail sales@clockaudio.demon.co.uk www.clockaudio.demon.co.uk