



## FEATURES

**400 WATT MONOLITHIC BI-AMPLIFICATION, 350 WATT LOW FREQUENCY AND 50 WATT HIGH FREQUENCY POWER**

**130 DB MAX SPL**

**WIDE DISPERSION, 80 X 60 LOW DISTORTION, CONSTANT DIRECTIVITY HORN**

**15" HIGH POWER WOOFER, 64MM EDGE WOUND ALUMINIUM COIL**

**1" NEODYMIUM, TITANIUM DOME, HIGH FREQUENCY DRIVER**

**ELECTRONIC EQUALIZATION, PHASE ALIGNMENT, LIMITER AND PROTECTION**

**MIC/LINE XLR AND JACK INPUT, XLR SIGNAL OUTPUT**

**BALTIC BIRCH CABINET WITH 2 SIDE HANDLES FOR EASY TRANSPORTATION AND POSITIONING**

**THREE M10 FLY POINTS AND STAND SOCKET**

**OPTIONAL REMOTE CONTROL**



# 4PRO 3001-A

**4PRO 3001-A is the perfect 2 way speaker for professional live sound situations where linearity in reproduction and extremely accurate high frequencies are required. Thanks to the versatility in live, playback and installation situations the 4PRO 3001-1 represents the perfect multipurpose solution.**

RCF 4PRO 3001-A is an active, wide dispersion 2 way sound reinforcement speaker. It integrates a high power 350 Watt amplifier, with complete electronic processor section and RCF low distortion, high power transducers. The result is a robust, high efficiency accurate system, producing unparalleled clarity and transparency for 15" and 1" 2 way speakers.

The new 15" inch woofer is the result of the latest refinement in years of RCF experience in compact 2 way speaker applications, resulting in an accurate reproduction of the midbass frequency range and a tight extended bass.

The compression driver uses a new 1.5" titanium dome in front of a low compression, optimised geometry, radial phase plug.

A generous 2 step class H design is used to power the low frequencies and the compression driver amplifier is a warm and clear class AB design.

All components are housed in a strong Baltic birch plywood enclosure where high density polystyrene end caps guarantee the maximum strength. Woofer and horn are protected from a full front, strong, powder coated, metal grille. The cabinet features three M10 threaded fly points, a 35 mm stand adaptor, two side handles for easy portability.

