











16m 110dB



FEATURES

950 WATT MONOLITHIC TRI-AMPLIFICATION, 600 WATT LOW FREQUENCY, 300 WATT MIDRANGE FREQUENCY AND 50 WATT HIGH FREQUENCY POWER.

134 DB MAX SPL

WIDE DISPERSION, 80 X 60 LOW DISTORTION, **MIDRANGE AND HIGH FREQUENCY HORNS**

2 X 12" HIGH POWER NEODYMIUM WOOFERS, 75MM INSIDE/OUTSIDE ALUMINIUM COIL

8" HIGH EFFICIENCY, LOW DISTORTION, **NEODYMIUM HORN LOADED MIDRANGE**

1" NEODYMIUM, TITANIUM DOME, HIGH **FREQUENCY DRIVER**

ELECTRONIC EQUALIZATION, PHASE ALIGNMENT, LIMITER AND PROTECTION

LINE COMBO XLR/JACK INPUT. XLR SIGNAL **OUTPUT**

BALTIC BIRCH CABINET WITH 2 SIDE HANDLES

4PRO 6001-A is a high output, medium throw, 3 way speaker designed for high demanding professional live sound systems. The incredible output and the extreme linearity and accuracy in reproduction make 4PRO 6001-A - a clear reference in its class. Perfect for Main PA, Side Fills, Night Clubs and Corporate Events

RCF 4PRO 6001-A is an active, medium throw, 3 way sound reinforcement speaker. It integrates a massive power 950 Watt amplifier, a complete electronic processor section and "full neodymium"

RCF low distortion, high power transducers.
RCF's unique 8" RCF Precision Series sealed basket midrange is specifically optimised to work in conjunction with the 4PRO 6001-A midrange horn. A massive neodymium magnet and a "compression driver level" assembly design has been dedicated to reach low distortion and dynamic properties for this transducer.

The compression driver uses a new 1.75" pure titanium dome in front of a low compression,

optimised geometry, 3 slot phase plug. This innovative design is powered from an extremely high flux neodymium magnet and offers incredible

precision in high frequency reproduction.

A high current 2 step class H design is used to power the low frequencies, mid and high frequencies are separately powered from class AB dedicated low distortion designs.

All components are housed in a trapezoidal, strong Baltic birch plywood enclosure. The cabinet features three 3 position fly-tracks and 2 M10 threaded points for rear kart. Two recessed side handles and one top handle guarantees easy

42R06001-A









